

DAVIS ISLAND TOWNHOMES

BUILDER SPECIFICATION SHEET

Foundation	*	8" CMU Stem Wall With Monolithic Footings
Masonry Slab	*	4" Thick With Fiber Mesh Or Metal Wire
Masonry Walls	*	8" CMU Foundation, Exterior Side Walls And Unit Partition Walls
Exterior Structural	*	6" Structural (SYP) Wood Studs On Front And Rear Walls
	*	8" CMU Exterior Side Walls And Unit Partition Walls
	*	TYP 3 Coat 7/8 Thick Stucco Over ½" Plywood With Tyvek House Wrap
Framing	*	Interior Walls 2x4 And Exterior 2x6 (SYP)
	*	9'-10' Ceiling Heights
Trusses	*	Floors Trusses: Engineered Wood Trusses 2' OC With 18" Depth
	*	Roof Trusses: Engineered Wood Trusses 24" OC.
Interior Stairs	*	Wood Flooring Materials On All Stairs Treads And Risers
Countertops	*	3cm Quartz
Cabinets	*	Solid Wood White Shaker Style Cabinets Throughout
Insulation	*	R-30 In Garage Ceiling And Third Floor Ceiling
	*	R-19 In Exterior Wall Framing
	*	Fi-Foil On All Masonry Walls
Roof	*	TPO Mechanically Fastened And Welded Over Isoboard
	*	GAF Dimensional Shingles
Front Doors	*	8' Masonite Door With Impact Glass
Overhead Garage Door	*	16' x 7' Flush Panel With Windows Top Panel
	*	8500W Side Mount Liftmaster Opener With 2 Clickers And Keypad
Windows	*	Residential Windows: MI Series 1620 With Impact Glass
Shower Enclosures	*	Frameless Glass In Master Shower And First Floor Shower Only
Mirrors	*	1/4' Clear Mirrors Standard In All Bathrooms
Bathroom Accessories	*	No Bathroom Accessories Such As Towel Bars Or TP Holders Are
		Included Or To Be Installed By Builder.
Stucco And Siding	*	5/8" Sand Finish Stucco On CMU Walls
	*	7/8" On Wood Framed Walls With 3/4" Projected Stucco Over Wire Lath
	*	Interior Garage And Demising Walls Are Block Finish Stucco

	❖ Hardie Cement Board Siding Front And Back Walls
Gypsum Drywall	❖ Finish: Orange Peel On Walls And Knockdown On Ceilings
	❖ Garage Ceiling 5/8" Type X Gypsum Drywall Board
Tile	❖ Garage To Unit Entry Steps
	❖ Bathrooms On Second Floor
	❖ Bathrooms On Third Floor
	Kitchen Backsplash
Wood Flooring	❖ All Interior Flooring Less Tile Areas
Painting	❖ Exterior: Primer And Two Coats
	 Exterior: One Color For Body And One Color For Trim
	❖ Interior: Prime And Two Coats
	 One Interior Neutral Color Throughout The Unit (Flat Paint)
	❖ Flat White Ceilings
	❖ White Semi-Gloss Latex On Trim And Doors
	❖ Sherwin Williams Paint Products
Closet Shelving	♦ MDF Wood Closet Shelving (White Color). Master Closets And Storage
	Or Linen Closets Are Excluded From The Builder Package
Appliances	 Stainless Steel Bosch (See Additional Design Spec Sheets)
HVAC	❖ 1st And 2nd Floor HVAC System: 3.5 Ton Comfortmaker Heat Pump
	Split System With 8 KW Auxiliary Heat Strip 14 SEER Rating.
	❖ 3rd Floor HVAC System: 1.5 Ton Comfortmaker Heat Pump Split
	System With 5KW Auxiliary Heat Strip 14 SEER Rating. Exhaust Fans: Broan 50 CFM
Plumbing	
Tumonig	 See Additional Design Spec Sheets Water Heater: Rinnai Tankless Gas Heater
Electrical	Residential: 200 AMP Service
	❖ LED Strip Lights Or Equivalent In Closets And Garage
	❖ Light Fixtures: See Additional Design Spec Sheets
	❖ 6" Recessed Can Lighting Package With LED Trims
Low Voltage	❖ Quad-Shielded Coaxial Cabling: Includes Dedicated Home Run And
	Video / Internet Runs Throughout The Unit And CAT5 Prewire. Project
	To Be Roughed In Only. Ends To Be Trimmed By Buyer LV Tech.