

BAYSHORE TOWNHOMES

BUILDER SPECIFICATION SHEET

Foundation	❖ 8" CMU Stem Wall Filled Solid With Monolithic Footings
	❖ Termite Treatment Applied Under The Building Slab
Masonry Slab	❖ 4" Thick With Fiber Mesh Or Metal Wire
Masonry Walls (CMU)	❖ 8" CMU Stem Wall, Exterior Perimeter Walls And Unit Partition Walls
Exterior Structural	6" Structural (SYP) Wood Studs On Front Facade Bump Outs Sheathed
	With 1/2" CDX Plywood And Then Wrapped With Henry Blueskin MVP
	❖ 8" CMU Exterior Walls And Unit Partition Walls Less Facade Bump Out
	❖ TYP 3 Coat ⁷ / ₈ " Stucco Over ⁵ / ₈ " CDX With Henry Blueskin House Wrap
Framing	 Interior Walls 2x4 (SPF) And Exterior Walls 2x6 (SYP)
	❖ 9'-10' Ceiling Heights (Varies Per Floor)
	 All Walls And Trusses Connected Per Hurricane Rated Building Codes
Trusses	❖ Floors Trusses: Engineered Wood Trusses 2' OC With 16" Depth
	❖ Roof Trusses: Engineered Wood Trusses 24" OC.
Interior Stairs	❖ LVP Wood Flooring Materials On All Stairs Treads And Risers
	 Buyer Will Have Limited Builder Provided Selection Options
Countertops	❖ 3cm Quartz With Waterfall Island Ends
	 Buyer Will Have Limited Builder Provided Selection Options
Cabinets	❖ Solid Wood Shaker Style Cabinets Throughout
	 Brushed Nickel Cabinet Hardware
	 Buyer Will Have Limited Builder Provided Color Selection Options
Insulation	❖ R-30 In Garage Ceiling And Third Floor Ceiling
	❖ R-19 In Exterior Wall Framing (No Interior Walls Or Floors Insulated)
	 Fi-Foil (M-Shield) On All Masonry Walls
Roof	❖ GAF Dimensional Shingles Over Peel & Stick Underlayment
Front Doors	❖ 8' Masonite Door With Impact Rated Glass
Overhead Garage Door	❖ 16' x 7' Impact Rated Door With Impact Rated Windows
	Garage Doors Will Have (2) Flood Vents In Them Per Code
	 3/4 HP Liftmaster Opener With 2 Clickers And Keypad
Windows	Residential Windows: CGI Sentinel (Bronze) With Impact Rated Glass
	❖ No Blinds, Curtains Or Shutters Of Any Type Are Included
Shower Enclosures	 Frameless Glass In Master Shower And First Floor Shower Only
II.	

Mirrors	*	1/4' Clear Mirrors Standard In All Bathrooms (No Frames)
Bathroom Accessories	*	Excludes All Bathroom Accessories Such As Towel Bars, Shower Rods
		Or TP Holders Are Included Or To Be Installed By Builder Whatsoever.
Stucco	*	5/8" Sand Finish Stucco On CMU Walls
	*	7/8" On Wood Framed Walls With 3/4" Projected Stucco Over Wire Lath
	*	Interior Garage And Demising Walls Painted Block Finish (No Stucco)
Gypsum Drywall	*	Finish: Orange Peel On Walls And Knockdown On Ceilings
	*	Garage Ceiling 5/8" Type X Gypsum Drywall Board
Tile	*	Bathroom On First Floor (Shower Walls & Floors)
	*	Bathrooms On Second And Third Floor (Shower Walls & Floors)
	*	All Shower & Bathtub Tile Will Be To The Ceiling In Wet Areas
	*	Kitchen Backsplash
	*	Buyer Will Have Limited Builder Provided Selection Options
Trim	*	Finger Joint 5 1/4" Baseboards
	*	Finger Joint 3 ¹ / ₄ " Door Casing
	*	Finger Joint Window Sills With Skirt Fully Jammed And Cased
	*	3-5 Panel Hollow Core Modern Interior Doors
	*	Brushed Nickel Door Hardware
LVP Flooring	*	LVP On All Interior Flooring Less Tile Areas
	*	Buyer Will Have Limited Builder Provided Selection Options
Painting	*	Exterior: Primer And Two Coats
	*	Exterior: One Color For Body And One Color For Trim
	*	Interior: Prime And Two Coats
	*	One Interior Neutral Color Throughout The Unit (Flat Paint)
	*	Buyer May Choose One Neutral Interior Wall Color Only
	*	Flat White Ceilings
	*	White Semi-Gloss Latex On Trim And Doors
	*	Sherwin Williams Paint Products
Closet Shelving	*	MDF Wood Closet Shelving (White Color). Master Closets And Storage
		Or Linen Closets Base Package Is Included With The Builder Package
	*	Closet Upgrade Packages Available (Upgrade Options)
Appliances	*	Stainless Steel Bosch Package (See Additional Design Spec Sheets)
	*	Appliance Package Includes (2) Mini Fridges Per Design Specs
	*	Excludes: Washer And Dryer (Buyer Must Purchase And Install)
HVAC	*	(1) 3.5 Ton Comfortmaker Heat Pump Split & Zoned System (Per Floor 2
		And Floor 3) With 5KW Auxiliary Heat Strip And 14 SEER Rating And
		(1) 1.5 TON System For The First Floor Only
	*	Thermostats Operable And Temperatures Controlled Per Floor Zoning
	*	Bathroom Exhaust Fans: Broam 50 CFM
Plumbing	*	See Additional Design Spec Sheets Rinnai Tankless Gas Water Heater (In Garage)

	Excludes: Water Softener, Water Filter, Booster And Recirc Pumps
	Of All Types. Buyers May Install After Closing As Desired
Electrical	❖ Residential: 200 AMP Service Panel Located In The Garage
	❖ LED Strip Lights Or Equivalent In Closets And Garage
	❖ Light Fixtures: See Additional Design Spec Sheets
	❖ 6" Recessed Can Lighting Package With LED Trims
	❖ Easy Hookup With Garage Location Of Panel For Electric Car Chargers
Low Voltage	❖ Quad-Shielded Coaxial Cabling: Includes Dedicated Home Run And
	Video / Internet Runs Throughout The Unit And CAT5 Prewire. Project
	To Be Roughed In Only. Ends To Be Trimmed By Buyer LV Tech.
	 Upgrade Packages Available For Early Buyers